

# Season Collection

## technical data sheet

### Country of Origin

China

### Installation System

Drop-Down

### Ready Made Parquet

Season Collection

### Composition

3-ply engineered parquet, wood moisture 8% (+/- 1%), 4 sides bevelled edges, top layer approx. 3 mm (+/- 10%), middle layer 9 mm and back layer 2 mm from poplar, max. 25% nested length per box.

### Specification

Oak wooden 1-strip flooring

### Grading

Rustic: knotty appearance with cracks and sapwood

### Packaging

Shrink wrapped, neutral black carton box with label stickers describing product specification. Installation and maintenance guide are included in every second box.

### Dimension

14 x 189 x 1,860 mm

### Thermal conductivity

0.13 W/mK

### Surface

Coated with oxidative natural oil

### Thermal passage value

0.12 m<sup>2</sup> K/W

### Packing units

8 planks

= 1 box

= 2.812 m<sup>2</sup>

40 boxes

= 1 pallet

= 112.493 m<sup>2</sup>

12 pallets

= 20' container

= 1,349.914 m<sup>2</sup>

24 pallets

= 40' container

= 2,699.828 m<sup>2</sup>



F.W. Barth & Co. GmbH,  
DE-41352 Korschenbroich  
13  
EN 14342 : 2005 + A1 : 2008  
ready-made 3-layer wood parquet

Density and Thickness 550 kg/m<sup>3</sup> ; 14 - 15 mm  
Reaction to fire D<sub>1</sub>-s1  
Release of formaldehyde E1  
Thermal conductivity 0.14 W/mK  
Biological durability Class 1